



CREATIVE



SCHEDA TECNICA PRODOTTO

OVIDIO

| PARAMETRI | UNITA' | NORMATIVA | | | | | | | | | | | | | | | |
|-------------------------------|------------------|------------|------------|------------|------------|------------|------------|------------|------------|------------|------------|------------|------------|------------|------------|------------|------------|
| Grammatura | g/m ² | ISO 536 | 90 | 100 | 105 | 120 | 125 | 145 | 180 | 200 | 225 | 250 | 280 | 300 | 350 | 400 | 480 |
| Spessore | µm | ISO 534 | 97 | 108 | 114 | 130 | 136 | 150 | 195 | 216 | 243 | 270 | 300 | 321 | 375 | 427 | 510 |
| Bianco ISO | % | ISO 2470-2 | 111 | 111 | 111 | 111 | 111 | 111 | 111 | 111 | 111 | 111 | 111 | 111 | 111 | 111 | 111 |
| Liscio Bendtsen (Tela) | ml/min | ISO 2494 | 50 | 50 | 50 | 50 | 50 | 50 | 50 | 50 | 50 | 50 | 50 | 50 | 50 | 50 | 50 |
| Ruvidità Bendtsen (Feltro) | ml/min | ISO 2494 | 50 | 50 | 50 | 50 | 50 | 50 | 50 | 50 | 50 | 50 | 50 | 50 | 50 | 50 | 50 |

I valori riportati sono puramente indicativi.

05/09/2018